



FREESTANDING VERSAFILLER®, REFRIGERATED ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER

MODEL PFCP10EBF-FVF

Suggested Specification

Model PFCP10EBF-FVF shall deliver 10.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall be freestanding in design with contactless activation for the dispensing of water and laminar flow. Bottle Filler alcove and cabinet finish shall be stainless steel.

Key bottle filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of microorganisms and mildew. Evaporator shall be high efficiency tank type and shall be encapsulated in insulation. An adjustable thermostat having an off position shall control refrigeration system. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



- Features:**
- Built-in 100 micron strainer stops particles before they enter the waterway
 - Waterways are lead-free in materials & construction
 - Contactless activation bottle filler with programmable auto shut off
 - High efficiency cooling system
 - High flow output of 1.1 gallons per minute for faster fill up
 - Built in drain - no drip tray to empty
 - Removable front panel for ease of filter change-out (not included)
 - Built-in filter monitor and bottle counter
 - Logos permanently formed into the alcove and stainless steel wrapper
 - LED lighted alcove

EQUIPARTS
Repair Parts Specialists

TOLL FREE: 800-442-6622
PITTSBURGH: 412-781-9100
www.equiparts.com

That Hard to Find Part is Right Here!

Filtration System:	OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor on Bottle Filler
Mounting Type:	Free Standing
Chilling Option:	10.0 gph*
Full Load Amps	5.0 amps
Rated Watts	500
Approx. Net Weight	71 lbs
Installation Location:	Indoor

Finishes

- Standard cabinet finish: Stainless steel

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



FREESTANDING VERSAFILLER[®], REFRIGERATED
ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER
MODEL PFCP10EBF-FVF

Accessories



OASIS VersaFilter III Replacement Cartridge

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



[View all filters and accessories](#)

EQUIPARTS
Repair Parts Specialists[®]

TOLL FREE: 800-442-6622


PITTSBURGH: 412-781-9100

www.equiparts.com

That Hard to Find Part is Right Here !






FREESTANDING VERSAFILLER®, REFRIGERATED
ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER
MODEL PFCPI0EBF-FV



ALL DIMENSIONS ARE IN INCHES.
DIMENSIONS IN BRACKETS () ARE IN MILLIMETERS.

ALLOW SPACE FOR VENTILATION AT THE
FRONT OF THE WATER COOLER AND THE
REAR IF SET IN AN ALCOVE OR NEAR A-CORNER.



EQUIPARTS
Repair Parts Specialists

TOLL FREE: 800-442-6622
PITTSBURGH: 412-781-9100
www.equiparts.com

That Hard to Find Part is Right Here!